

# K-9000

“Touch the world best POS system, K-POS Series”

K-9000 is designed to provide outstanding performance  
for your business and to protect your business.






### High Performance

- High-performance CPU loaded
- Vivid high-definition screen using LED technology
- Low-noise and low-heat using fan-less type



### Stylish Design

- Polished appearance of having tender curve



### Slim & Compact

- Ultra-thin and sleek exterior

### Simple & Easy Maintenance

- Easy assembly & disassembly without tools
- Convenient access to Mother Board

## K-9000

- Premium POS system designed for hospitality and retail
- Combined high technology and sleek design
- Maximum reliability
- Industry-leading durability and serviceability
- Vivid LED screen for the best view
- Tools-free maintenance with great ease



### Product reliability & safety

Proven product reliability and safety through EMC test, KC, CE & FCC by Authorized Testing and Certification Bodies

### Green IT

Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



## K-9000

www.okpos.co.kr



## Specification

Item	Specification	
Main	Formfactor	170 mm(W) x 170mm(L): Embedded Mini ITX Platform
	CPU	Onboard Intel Celeron 1037U 1.8GHz (Dual Core)
	Chipset	Intel NM70 Express Chipset
	Memory	DDR3 SODIMM 2GB (up to 8GB by 2 x Slots)
	Storage	2.5" SATA-II 320GB HDD
Primary Display	LCD	15-inch TFT LED LCD (350cd), LVDS Interface
	Resolution	1024 x 768
	Touch	15-inch 5-Wire Resistive Frame Type, Serial Interface
I/O Port	Indicator	2 x LED
	Speaker	1 x 1W
	USB	6 x USB (Rear: 4 x USB, Side: 2 x USB)
	Serial	4 x RS-232C (3 x Powered DSUB-9, 1 x RJ-45)
		COM 1~4: 0/5/12V by BIOS select
	PS/2	1 x Keyboard or Mouse
	LAN	1 x Gigabit LAN
	VGA	1 x RGB
	Audio	2 ports (1 x Mic-in, 1 x Line-out)
Power	DC-IN	External 60W Adapter
		Input AC 100~240V/50~60Hz, Output DC 12V/5A
User Environment	Temperature	Operating -25 to 65, Storage -35 to 75
Size	Dimmension	341 x 345 x 209 (WxDxH)
	Weight	6.6 Kg (without MSR) / 6.9 kg (with MSR)
Optional Peripherals	MSR	ISO 1,2,3 Tracks Reading
	OS	POSReady2009 / POSReady7
	Storage	SATA-III HDD 320GB / SSD 64GB
	2nd Display	15-inch LED LCD (1024 x 768)
		9.7-inch TFT LCD (1024 x 768)

This specification can be changed without Prior notice

**OKPOS**  
No.1 Total Solution Provider

# 801-802, Ace High-end Tower 6th, Gasan-dong, Geumcheon-gu, Seoul, Korea (153 - 801)  
Tel +82-1566-9051, Fax +82-2-6299-5447, URL www.okpos.co.kr/eng

ver. KPOS\_201312\_EA

made in Korea